Eaton's Aeroquip® MatchMate® Global GH663 hose puts the pressure on Flextral with its Triple Crown Advantage.

Eaton's engineered technology improved the design of select Aeroquip hydraulic hoses which provide a distinct competitive advantage in three key areas.

1 Pressure
Improved working pressures to a higher performance level!

+

2 Temperature
Improved working temperatures to a higher performance level!

+

3 Abrasion Resistance
Better abrasion resistance with Aeroquip DURA-TUFF™ cover than traditional rubber covered hose

= Aeroquip Triple Crown Advantage

Indicates a product identified as an Aeroquip Triple Crown Advantage hose product.
For more information go to www.Eaton.com/TripleCrownAdvantage

Features and Benefits

- 1-Wire braided construction
- ***Exceeds*** EN853 Type 1SN performance
- ***Exceeds*** SAE 100R1 AT Type S performance
- DURA-TUFF™ cover - more abrasion resistant than a traditional rubber covered hose.
- Compatible with all existing Aeroquip crimp machines
- Temperature rating of -40˚C to +127˚C (-40˚F to +260˚F) – Highest rating in the market

Qualified Fittings

- TTC Series (non-skive) and Global Braided (skive) nipples with 1SA sockets

Comparison of Aeroquip GH663 v. Flextral GX Series Hose.
*Maximum operating pressure shown in psi.

Aeroquip's Part #	GH663 Pressure*	Flextral's Part #	Flextral's GX Series Pressure*	GH663 Advantage
GH663-4	3700	GX-04	3265	+ **13%**
GH663-6	3400	GX-06	2610	+ **30%**
GH663-8	2900	GX-08	2320	+ **25%**
GH663-12	2000	GX-12	1525	+ **31%**
GH663-16	1500	GX-16	1275	+ **18%**
GH663-20	1000	GX-20	915	+ **9%**
GH663-24	750	GX-24	725	+ **3%**
GH663-32	600	GX-32	580	+ **3%**

Flextral maximum operating pressure data sourced from Flextral Catalog Third Edition.
Flextral is a registered trademark of OPG Inc.

=

+17%

Triple Crown Advantage: 17% average higher pressures over Flextral

EATON
Powering Business Worldwide

Eaton Corporation
For confidential use only

© 2010 Eaton Corporation
All Rights Reserved.
Document No. A-HOBR-TH021-E
January 2010