Eaton Winner – EC110

EN853 1SN

Part Number	DN	Hose I.D.		Hose O.D.		Maximum Operating Pressure		Minimum Burst Pressure		Minimum Bend Radius		Weight	
		mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lb/ft
EC110-04	6	6,4	0.25	14,1	0.56	225	3,250	900	13,000	100,0	3.99	0.22	0.15
EC110-06	10	9,5	0.38	18,1	0.71	180	2,600	720	10,400	130,0	5.12	0.33	0.22
EC110-08	12	12,7	0.50	21,4	0.84	160	2,300	640	9,200	180,0	7.09	0.41	0.28
EC110-12	19	19,0	0.75	28,5	1.12	105	1,525	420	6,100	240,0	9.45	0.59	0.40
EC110-16	25	25,4	1.00	36,6	1.44	88	1,275	352	5,100	300,0	11.81	0.87	0.58

Construction

Synthetic rubber tube, single wire braid reinforcement, and black synthetic rubber cover
MSHA Approved

Operating Temperature Range

-40°C to +100°C
(-40°F to +212°F)

Application

Hydraulic system service with petroleum and water-based fluids for general industrial service. For more information on specific fluid applications contact Eaton Corporation.

Fitting Reference

Crimp
Approved with Winner two piece non-skive fittings (15611, 24211, 24211D, 24241, 24291, 26711, 26711D, 26741 and 26791)

Powering Business Worldwide

Eaton Winner – EC210

EN853 2SN

Part Number	DN	Hose I.D.		Hose O.D.		Maximum Operating Pressure		Minimum Burst Pressure		Minimum Bend Radius		Weight	
		mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lb/ft
EC210-04	6	6,4	0.25	15,7	0.62	400	5,800	1600	23,200	100,0	3.94	0.38	0.26
EC210-06	10	9,5	0.38	19,7	0.78	330	4,800	1320	19,200	130,0	5.12	0.54	0.36
EC210-08	12	12,7	0.50	23,0	0.91	275	4,000	1100	16,000	180,0	7.09	0.64	0.43
EC210-12	19	19,0	0.75	30,1	1.09	215	3,125	860	12,500	240,0	9.45	0.93	0.62
EC210-16	25	25,4	1.00	38,9	1.53	165	2,400	660	9,600	300,0	11.81	1.29	0.87

Construction

Synthetic rubber tube, two wire braid reinforcement, and black synthetic rubber cover
MSHA Approved

Operating Temperature Range

-40°C to +100°C
(-40°F to +212°F)

Application

Hydraulic system service with petroleum and water-based fluids for general industrial service. For more information on specific fluid applications contact Eaton Corporation.

Fitting Reference

Crimp
Approved with Winner two piece non-skive fittings (15611, 24211, 24211D, 24241, 24291, 26711, 26711D, 26741 and 26791)

Eaton
Hydraulics Group USA
14615 Lone Oak Road
Eden Prairie, MN 55344
USA
Tel: 952-937-9800
Fax: 952-294-7722
www.eaton.com/hydraulics

Eaton
Hydraulics Group Europe
Route de la Longeraie 7
1110 Morges
Switzerland
Tel: +41 (0) 21 811 4600
Fax: +41 (0) 21 811 4601

Eaton
Hydraulics Group Asia Pacific
Eaton Building
No.7 Lane 280 Linhong Road
Changning District,
Shanghai 200335
China
Tel: (+86 21) 5200 0099
Fax: (+86 21) 2230 7240

Powering Business Worldwide

© 2012 Eaton Corporation
All Rights Reserved
Printed in USA
Document No. E-HOBR-MB001-E2
November 2012