Features and Benefits

- Designed to be used with standard beverage industry fittings
- Suitable for potable water
- Resistant to flavor migration
- NSF-51 & NSF-61 listed
- Available in custom colors
- Short custom orders of tube, hose, and bundles
- Materials comply with FDA Specifications
- RoHS compliant materials
- Temperature Range: -40°C to +65°C (-40°F to +150°F)
- Available for shipment out of the Eaton Guelph, ON facility

Flo-Guard Plus continues to be an excellent choice when you are looking for the entire package of ease of installation, maximum flexibility, and flavor protection.

Powering Business Worldwide

Eaton Flo-Guard® Plus

Eaton is proud to announce the introduction of the Flo-Guard Plus line of beverage tubing, hose and bundle products. Our team of engineers has designed, and verified through testing, changes to our Flo-Guard Plus single lines and bundles. These changes will improve overall product performance based on market changes in the syrup and potable water industries.

The tubes and hoses in the Flo-Guard Plus product lines still use a polyamide contact layer. However, to improve the sensory performance and barrier protection, new thermoplastic materials are being used. To further improve performance and protection, a polyester film is applied over the tubes and hoses.

In order to make the transition convenient and seamless, part numbers and packaging will remain the same.

Flo-Guard Plus continues to be an excellent choice when you are looking for the entire package of ease of installation, maximum flexibility, and flavor protection.

Flo-Guard Plus can be thermoformed in order to increase routing efficiency and reduce fitting usage.

The polyamide lined hoses and tubes are available in standard sizes .265" and .375" ID sizes. Custom size configurations are also available from < .125" up to .750" ID sizes.

Eaton Flo-Guard® Plus

Hose Part Number	Color	Nominal I.D. mm	Nominal I.D. in	Nominal O.D. mm	Nominal O.D. in	Min. Bend Radius mm	Min. Bend Radius in	Max Working Pressure @72° F bar	Max Working Pressure @72° F psi	Weight per 100 ft kg	Weight per 100 ft lbs	Standard Length m	Standard Length ft	Packaging	Clamp Size mm
63-0400-00	Natural	6.7	.265	13.1	.517	38.1	1.5	0.7	300	22.95	6.5	152.40	500	Spool/Boxed	14.5
63-0400-01	Natural	6.7	.265	11.6	.457	45.7	1.8	20.7	300	2.81	6.2	152.40	500	Spool/Boxed	13.3
63-0404-00	Red	6.7	.265	13.1	.517	38.1	1.5	20.7	300	2.95	6.5	152.40	500	Spool/Boxed	14.5
63-0404-01	Red	6.7	.265	11.6	.457	45.7	1.8	20.7	300	2.81	6.2	152.40	500	Spool/Boxed	13.3
63-0406-00	Blue	6.7	.265	13.1	.517	38.1	1.5	20.7	300	2.95	6.5	152.40	500	Spool/Boxed	14.4
63-0406-01	Blue	6.7	.265	11.6	.457	45.7	1.8	20.7	300	2.81	6.2	152.40	500	Spool/Boxed	13.3
63-0600-00	Natural	9.5	.375	16.1	.635	50.8	2.0	20.7	300	4.08	9.0	91.44	300	Spool/Boxed	17.0
63-0600-01	Natural	9.5	.375	15.1	.593	63.5	2.5	20.7	300	3.90	8.6	91.44	300	Spool/Boxed	15.7
63-0604-00	Red	9.5	.375	16.1	.635	50.8	2.0	20.7	300	4.08	9.0	91.44	300	Spool/Boxed	17.0
63-0604-01	Red	9.5	.375	15.1	.593	63.5	2.5	20.7	300	3.90	8.6	91.44	300	Spool/Boxed	15.7
63-0606-00	Blue	9.5	.375	16.1	.635	50.8	2.0	20.7	300	4.08	9.0	91.44	300	Spool/Boxed	17.0
63-0606-01	Blue	9.5	.375	15.1	.593	63.5	2.5	20.7	300	3.90	8.6	91.44	300	Spool/Boxed	15.7

All items are Made to Order and subject to minimum runs. Shorter runs available with price premium.

Tube Part Number	Color	Nominal I.D. mm	Nominal I.D. in	Nominal O.D. mm	Nominal O.D. in	Min. Bend Radius mm	Min. Bend Radius in	Max Working Pressure @72° F bar	Max Working Pressure @72° F psi	Weight per 100 ft kg	Weight per 100 ft lbs	Standard Length m	Standard Length ft	Packaging	Clamp Size mm
58-0400-00*	Natural	6.7	.265	9.5	.375	50.8	2.0	8.6	125	1.22	2.7	152.40	500	Spool/Boxed	10.5
58-0404-00	Red	6.7	.265	9.5	.375	50.8	2.0	8.6	125	1.22	2.7	152.40	500	Spool/Boxed	10.5
58-0406-00	Blue	6.7	.265	9.5	.375	50.8	2.0	8.6	125	1.22	2.7	152.40	500	Spool/Boxed	10.5
58-0600-00*	Natural	9.5	.375	12.7	.500	76.2	3.0	6.8	100	1.68	3.7	91.44	300	Spool/Boxed	14.0
58-0604-00	Red	9.5	.375	12.7	.500	76.2	3.0	6.8	100	1.68	3.7	91.44	300	Spool/Boxed	14.0
58-0606-00	Blue	9.5	.375	12.7	.500	76.2	3.0	6.8	100	1.68	3.7	91.44	300	Spool/Boxed	14.0

*Standard stocked items. All other items are Made to Order and subject to minimum runs. Shorter runs available with price premium.

Bundle Part Number	Description	Standard Length (ft)	Packaging
Type 73 - Cabled Bundles			
73-0800-31	(8) .375" ID x .500" OD tubes	100	Coil
73-0800-32		200	Coil
73-0800-35		500	Reel
73-0820-31	(8) .265" ID x .375" OD tubes w/ (2) .375" ID x .500" OD tubes	100	Coil
73-0820-32		200	Coil
73-0820-35		500	Reel
73-0100-31	(10) .375" ID x .500" OD tubes	100	Coil
73-0100-32		200	Coil
73-0100-35		500	Reel
73-0804-31	(8) .265" ID x .375" OD tubes w/ (4) .375" ID x .500" OD tubes	100	Coil
73-0804-32		200	Coil
73-0804-35		500	Reel
73-0210-31	(10) .265" ID x .375" OD tubes w/ (2) .375" ID x .500" OD tubes	100	Coil
73-0210-32		200	Coil
73-0210-35		500	Reel
73-0120-31	(12) .375" ID x .500" OD tubes	100	Coil
73-0120-32		200	Coil
73-0120-35		500	Reel

Bundle Part Number	Description	Standard Length (ft)	Packaging
Type 73 - Cabled Bundles (continued)			
73-0410-31	(10) .265" ID x .375" OD tubes w/ (4) .375" ID x .500" OD tubes	100	Coil
73-0410-32		200	Coil
73-0410-35		500	Reel
73-0140-31	(14) .375" ID x .500" OD tubes	100	Coil
73-0140-32		200	Coil
73-0140-35		500	Reel
Type 78 - Insulated Beer Bundles			
78-B006-94	(2) .375" ID re-circ lines (4) .375" ID x .500" OD product lines	400	Reel
78-B008-93	(2) .375" ID re-circ lines (6) .375" ID x .500" OD product lines	300	Reel
78-B010-90	(2) .375" ID re-circ lines (8) .375" ID x .500" OD product lines	500	Reel
78-B014-92	(4) .375" ID re-circ lines (10) .375" ID x .500" OD product lines	200	Reel
78-B016-91	(4) .375" ID re-circ lines (12) .375" ID x .500" OD product lines	400	Reel

Eaton
Hydraulics Business USA
14615 Lone Oak Road
Eden Prairie, MN 55344
USA
Tel: 952-937-9800
Fax: 952-294-7722
www.eaton.com/hydraulics

Eaton
Hydraulics Business Europe
Route de la Longeraie 7
1110 Morges
Switzerland
Tel: +41 (0) 21 811 4600
Fax: +41 (0) 21 811 4601

Eaton
Hydraulics Business Asia Pacific
11th Floor Hong Kong New World Tower
300 Huaihai Zhong Road
Shanghai 200021
China
Tel: 86-21-6387-9988
Fax: 86-21-6335-3912

Eaton
Eaton Business USA
115 Lena Dr.
Aurora, OH 44202
USA
Tel: 330-562-9111
Toll Free: 800-837-1467
Fax: 330-274-0473

Eaton
Hydraulics Business
49 Cutten Place
Guelph, Ontario N1G4Z7
Canada
Tel: 519-836-5575
Toll Free: 877-662-8823
Fax: 519-836-5412

Powering Business Worldwide

© 2010 Eaton Corporation
All Rights Reserved

Printed in USA
Document No. E-HOBV-MS002-E
June 2010