


AK1

1000 A Transient voltage suppressor



Product features

- Bi-directional
- Low slope resistance
- Very low clamping voltage
- Sharp breakdown voltage
- Glass passivated junction
- Snapback technology for superior clamping factor
- High temperature wave soldering: +265 °C /10 s at terminal

Applications

- Consumer electronics
- Telecommunications
- Computing and servers
- Appliances
- Industrial automation
- Vac line protection

Environmental compliance and general specifications



Ordering part number

Family name AK1
 V_R voltage -076
 Bi-/Uni-Directional C
 (C=Bi)

Alternate ordering part number

Family name AK1 E
 Eaton designator (optional) -076
 V_R voltage C
 Bi-/Uni-Directional
 (C=Bi)

PIN configuration




Powering Business Worldwide

Absolute maximum ratings

(+25 °C, RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak current rating per 8/20 μ s IEC 61000-4-5	I_{PP}	1	kA
Operating junction temperature range	T_J	-55 to +125	°C
Storage temperature range	T_{STG}	-55 to +150	°C

Mechanical parameters- mm




Dimension		Inches	Millimeters
A		0.951 ± 0.039	24.15 ± 1.00
B		0.094 ± 0.024	2.40 ± 0.60
C		0.236 ± 0.039	6.00 ± 1.00
D		0.570 max	14.48 max
E		0.050 ± 0.002	1.27 ± 0.05
F		0.500 max	12.70 max
G	076C	0.169 ± 0.047	4.30 ± 1.20
	380C to 430C	0.287 ± 0.047	7.30 ± 1.20
L ₁ /L ₂	L1=L2 tolerance ± 0.047 inch (± 1.20 mm)		


Part marking

Standard part number marking


Alternate part number marking




Part number:
AK1-076C



Part number:
AK1E-076C



Part number:
AK1-380C
AK1-430C



Part number:
AK1E-380C
AK1E-430C

Electrical characteristics (+25 °C)

Part number	V_R (V)	$V_{BR} @ I_T$ min (V)	max (V)	I_T (mA)	$I_R @ V_R$ (μ A)	$V_C @ I_{PP}$ (V)	I_{PP} (A)
AK1-076C	76	85	95	10	10	140	1000
AK1-380C	380	401	443	10	10	520	1000
AK1-430C	430	440	490	10	10	625	1000

Note: Standard part numbers listed


Alternate part numbers have the addition of an E. Example standard part number AK1-076C, Alternate part number AK1E-076C

Packaging information (mm)


Bulk: 56 parts per box

Ratings and V-I characteristic curves (+25 °C unless otherwise noted)

V- I curve characteristics (Bi-directional)



Typical V_{BR} vs junction temperature



Surge waveform: 8/20 μ s

V_R : Stand-off voltage – Maximum voltage that can be applied


V_{BR} : Breakdown voltage

V_C : Clamping voltage – Peak voltage measured across the suppressor at a specified I_{PP}


I_R : Reverse leakage current

I_T : Test current


Pulse waveform



Pulse derating curve



Wave solder profile



Reference EN 61760-1:2006

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat		
• Temperature min. (T_{smin})	100 °C	100 °C
• Temperature typ. (T_{styp})	120 °C	120 °C
• Temperature max. (T_{smax})	130 °C	130 °C
• Time (T_{smin} to T_{smax}) (t_s)	70 seconds	70 seconds
Δ preheat to max Temperature	150 °C max.	150 °C max.
Peak temperature (T_p)*	235 °C – 260 °C	250 °C – 265 °C
Time at peak temperature (t_p)	10 seconds max 5 seconds max each wave	10 seconds max 5 seconds max each wave
Ramp-down rate	~ 2 K/s min ~3.5 K/s typ ~5 K/s max	~ 2 K/s min ~3.5 K/s typ ~5 K/s max
Time 25 °C to 25 °C	4 minutes	4 minutes

Manual solder

+350 °C (4-5 seconds by soldering iron), generally manual/hand soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2024 Eaton
All Rights Reserved
Printed in USA
Publication No. 11208
September 2024

Eaton is a registered trademark.

All other trademarks are property
of their respective owners.

Follow us on social media to get the
latest product and support information.

