


PTxx

Surface mount PTC thermistor



Product features

- Highly reliable monolithic structure, ideal for high density SMT installation
- Ideal for overheat sensing applications
- 0603 (1608 metric) and 0805 (2012 metric) surface mount package
- Superior heat resistance
- Excellent thermal response
- Moisture sensitivity level (MSL): 1


Applications

- Overheat sensing
- Industrial process control
- Commercial appliances
- Battery, supercapacitor and energy storage systems
- Uninterruptible power supplies
- Consumer appliances
- Medical devices
- Heating, ventilation and air conditioning, refrigeration (HVACR)
- Food service equipment
- IoT

Environmental compliance and general specifications



Table 1. Part numbering




A 3D perspective diagram of a rectangular block. The top horizontal edge is labeled $L1$. The front horizontal edge is divided into three segments: the leftmost is labeled $L2$, the middle is shaded gray and labeled $L3$, and the rightmost is labeled $L3$. The vertical edge on the left is labeled H . The depth edge on the top left is labeled W .

A diagram of a rectangular block. The width of the block is labeled 'A', the height is labeled 'B', and the depth (thickness) is labeled 'C'.

Packaging information- mm

Supplied in tape and reel on a 7.0" diameter reel (EIA-481 compliant)

Size	Quantity
0603	4K
0805	4K



Dimension	0603	0805
E1	1.75±0.1	1.75±0.1
F	3.5±0.05	3.5±0.05
P2	2.0±0.05	2.0±0.05
D0	1.5±0.1	1.5±0.1
P0	4.0±0.1	4.0±0.1
W	8.0±0.3	8.0±0.3
P1	4.0±0.1	4.0±0.1
A0	1.0±0.2	1.4±0.2
B0	1.8±0.2	2.2±0.2
T	1.1max	1.1max

Electrical specifications

Part number	Resistance (Ω)	Curie temperature (°C)	Sensing temperature (4.7 kΩ) (°C)	Sensing temperature (47 kΩ) (°C)	Maximum voltage (Vdc)	Operating temperature (°C)
PT06R472P50	470±50%	50	65±5	80±7	32	-20 to +90 °C
PT06R472P60	470±50%	60	75±5	90±7	32	-20 to +100 °C
PT06R472P70	470±50%	70	85±5	100±7	32	-20 to +110 °C
PT06R472P80	470±50%	80	95±5	110±7	32	-20 to +120 °C
PT06R472P90	470±50%	90	105±5	120±7	32	-20 to +130 °C
PT06R472P100	470±50%	100	115±5	130±7	32	-20 to +140 °C
PT06R472P110	470±50%	110	125±5	140±7	32	-20 to +150 °C
PT06R472P120	470±50%	120	135±5	150±7	32	-20 to +160 °C
PT08R472P50	470±50%	50	65±5	80±7	32	-20 to +90 °C
PT08R472P60	470±50%	60	75±5	90±7	32	-20 to +100 °C
PT08R472P70	470±50%	70	85±5	100±7	32	-20 to +110 °C
PT08R472P80	470±50%	80	95±5	110±7	32	-20 to +120 °C
PT08R472P90	470±50%	90	105±5	120±7	32	-20 to +130 °C
PT08R472P100	470±50%	100	115±5	130±7	32	-20 to +140 °C
PT08R472P110	470±50%	110	125±5	140±7	32	-20 to +150 °C
PT08R472P120	470±50%	120	135±5	150±7	32	-20 to +160 °C

Solder reflow profile




Table 1 - Standard SnPb solder (T_c)

Package thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) free solder (T_c)

Package thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference J-STD-020

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat and soak		
• Temperature min. (T_{smin})	100 °C	150 °C
• Temperature max. (T_{smax})	150 °C	200 °C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds	60-120 seconds
Ramp up rate T_L to T_p	3 °C/ second max.	3 °C/ second max.
Liquidous temperature (T_L)	183 °C	217 °C
Time (t_L) maintained above T_L	60-150 seconds	60-150 seconds
Peak package body temperature (T_p)*	Table 1	Table 2
Time (t_p)* within 5 °C of the specified classification temperature (T_c)	20 seconds*	30 seconds*
Ramp-down rate (T_p to T_L)	6 °C/ second max.	6 °C/ second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

Manual solder

Soldering iron power 30 W max., pre-heating: +150°C/60 sec, soldering tip temperature: +350 °C max for 3 sec max.1 time solder iron max. Generally manual soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2022 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1111 BU-ELX21123
January 2022

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

