

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)

NOTE

This E50DR19 Series A1 side rotary operating head has an operating temperature range between - 54°C to 79°C (-65°F to 175°F). It is intended for use only with E50SA single pole and E50SB double pole switch bodies.

No attempt should be made to add lubrication to this equipment.

P16530

EAT•N

1110 Rev. (001)