



Save time and money with a simplified connection that meets special NEC® requirements.

**Designed for time Savings:**

- Prewired - ready to install
- Factory installed ground bar - no kits required
- Factory assembled circuit breaker
- Bottom fed or top fed using a raintight hub
- Outdoor enclosure

**Designed for Safety:**

- Padlockable door prevents unauthorized persons from switching the breaker off
- Push to trip button easily allows routine testing of the breaker
- Meets code requirements for a safety disconnect



**Warranty:**

- Limited lifetime warranty on Type CH hot tub panels, thermal magnetic, and GFCI branch circuit breakers.
- 10 year limited warranty on Type BR hot tub panels, thermal magnetic, and GFCI branch breakers.

**Ordering Information:**

- Contact your local Eaton representative today for more information on Eaton's Hot Tub Panels, or visit [www.eaton.com](http://www.eaton.com).



The National Electrical Code is a registered trademark of the National Fire Protection Association.

UL is a registered trademark of Underwriters Laboratories.

All other trademarks are property of their respective owners.

**Eaton Corporation**  
 Electrical Sector  
 1111 Superior Ave.  
 Cleveland, OH 44114  
 United States  
 877-ETN-CARE (877-386-2273)  
 Eaton.com

© 2011 Eaton Corporation  
 All Rights Reserved  
 Printed in USA  
 Publication No. SA00308001E  
 August 2011

Eaton Hot Tub Panels

# Hot Tub Panels



# Eaton Hot Tub Panels are available in two types

## Type BR

### Features:

- 10 year warranty
- UL® Listed
- Factory installed two pole ground fault circuit interrupter (GFCI)



Type BR Two Pole GFCI

### Product Selection

Catalog Number	Main Amp Rating	Enclosure Type	Dimensions	Factory Installed Circuit Breaker	Wire Size Range Cu/Al 60°C or 75°C for Main Lugs
BR40SPA	40	Outdoor	9.75"H x 5.0"W x 4.0"D	GFCB240	#8 - #2
BR50SPA	50	Outdoor	9.75"H x 5.0"W x 4.0"D	GFCB250	#8 - #2

## Type CH

### Features:

- Two extra circuits for additional loads
- Limited lifetime warranty
- UL Listed
- Tough powder coated galvanized steel enclosure
- Factory installed two pole ground fault circuit interrupter (GFCI)



Type CH Two Pole GFCI

### Product Selection

Catalog Number	Main Amp Rating	No. of Extra Circuits Available	Enclosure Type	Dimensions	Factory Installed Circuit Breaker	Wire Size Range Cu/Al 60°C or 75°C for Main Lugs
CH30SPA	30	2	Outdoor	11.75"H x 6.75"W x 4.25"D	CH230GF	#14 - 1/0
CH40SPA	40	2	Outdoor	11.75"H x 6.75"W x 4.25"D	CH240GF	#14 - 1/0
CH50SPA	50	2	Outdoor	11.75"H x 6.75"W x 4.25"D	CH250GF	#14 - 1/0
CH60SPA	60	2	Outdoor	11.75"H x 6.75"W x 4.25"D	CH260GF	#14 - 1/0

### The National Electrical Code® safety requirements for spa pumps:

- GFCI protection
- Visible disconnect

