



TIME-CURRENT CHARACTERISTIC CURVES
 MINIMUM MELT
 23 KV NXC (CAPACITOR) FUSE

DRAWN BY: SES
 DATE: 3-7-00
 REPLACES: 7/95
 DWG NO.: 42 3925 | B | 00

CHK'D: _____
 DATE: _____
 TESTS MADE AT LOW Volts ac at HIGH pf at 25°C with no initial load
 Standards used as basis for data: ANSI C37.47-1991 (R1992)
 MINIMUM TEST POINTS PLOTTED SO VARIATIONS SHOULD BE PLUS
 THIS DRAWING WAS PRODUCED ON A CAD SYSTEM, ANY MANUAL REVISION WILL VOID IT.

Reference Data
 R240-91-39
 Page 1 of 2



TIME-CURRENT CHARACTERISTIC CURVES
 MAXIMUM CLEAR
 23 KV NXC (CAPACITOR) FUSE

DRAWN BY: SES
 DATE: 3-7-00
 REPLACES: 7/95
 DWG NO.: 42 3925 | B | 00

CHK'D: _____
 DATE: _____
 TESTS MADE AT RATED Volts ac at LOW pf at 25°C with no initial load
 Standards used as basis for data: ANSI C37.47-1991 (R1992)
 MINIMUM TEST POINTS PLOTTED SO VARIATIONS SHOULD BE MINUS
 THIS DRAWING WAS PRODUCED ON A CAD SYSTEM, ANY MANUAL REVISION WILL VOID IT.

Reference Data
 R240-91-39
 Page 2 of 2